

# CERAMICHE SUPERGRES

GRES PORCELLANATO \_ Grès cérame \_ Feinsteinzeug \_ Porcelain stoneware \_ Gres porcelánico \_ Керамогранит  
EN 14411 Allegato G Piastrelle di ceramica pressate a secco con basso assorbimento d'acqua ( $E \leq 0,5 \%$ )  
Gruppo B la UGL (non smaltate, non émaillé, unglasierte, unglazed, no esmaltado, Неглазурованные)

10 mm



*Habitat 60x60RT - 24"x24"*  
*Habitat 60x60RT lappato - 24"x24"*



*Habitat 45x90RT - 18"x36"*



*Habitat 30x60RT - 12"x24"*  
*Habitat 30x60RT lappato - 12"x24"*



*Habitat mosaico 30x30RT - 12"x12"*



*Habitat 45x45RT - 18"x18"*  
*Habitat 45x45RT lappato - 18"x18"*



ECOLABEL  
IT/21/01

Per la posa del materiale rettificato si consiglia una fuga di 2 mm \_ Pour poser du matériel rectifié nous vous conseillons un joint de 2 mm  
As for rectified materials, it is strongly recommended a 2 mm joint installation \_ Für die Verlegung des kalibrierten Materials empfehlen wir 2 mm Fuge  
Para la colocación de material rectificado se aconsejan juntas de 2 mm \_ Ретифицированную плитку рекомендуется укладывать со швом 2 мм.

 10 mm




*Nature 60x60RT - 24"x24"*  
*Nature 60x60RT lappato - 24"x24"*



*Nature 45x90RT - 18"x36"*



*Nature 30x60RT - 12"x24"*  
*Nature 30x60RT lappato - 12"x24"*



*Nature mosaico 30x30RT - 12"x12"*



*Nature 45x45RT - 18"x18"*  
*Nature 45x45RT lappato - 18"x18"*



ECOLABEL  
IT/21/01

GRES PORCELLANATO \_ Grès cérame \_ Feinsteinzeug \_ Porcelain stoneware \_ Gres porcelánico \_ Керамогранит  
EN 14411 Allegato G Piastrelle di ceramica pressate a secco con basso assorbimento d'acqua ( $E \leq 0,5 \%$ )  
Gruppo B la UGL (non smaltate, non émaillé, unglasierte, unglazed, no esmaltado, Неглазурованные)


10 mm



*Energy 60x60RT - 24"x24"*  
*Energy 60x60RT lappato - 24"x24"*



*Energy 30x60RT - 12"x24"*  
*Energy 30x60RT lappato - 12"x24"*



*Energy mosaico 30x30RT - 12"x12"*

*Energy 45x45RT - 18"x18"*  
*Energy 45x45RT lappato - 18"x18"*



Per la posa del materiale rettificato si consiglia una fuga di 2 mm \_ Pour poser du matériel rectifié nous vous conseillons un joint de 2 mm  
As for rectified materials, it is strongly recommended a 2 mm joint installation \_ Für die Verlegung des kalibrierten Materials empfehlen wir 2 mm Fuge  
Para la colocación de material rectificado se aconsejan juntas de 2 mm \_ Ретифицированную плитку рекомендуется укладывать со швом 2 мм.

 10 mm



*People 45x90RT - 18"x36"*



*People 30x60RT - 12"x24"*  
*People 30x60RT lappato - 12"x24"*



*People mosaico 30x30RT - 12"x12"*



*People 45x45RT - 18"x18"*  
*People 45x45RT lappato - 18"x18"*




ECOLABEL  
IT/21/01

*Profilo inox 0,5x50 - 0,2"x20"*



*Battiscopa 9,5x60 - 3,7"x24" (\*)*  
*Battiscopa 9,5x60 lappato - 3,7"x24" (\*)*



*Battiscopa 8,5x45 - 3,3"x18" (\*)*  
*Battiscopa 8,5x45 lappato - 3,3"x18" (\*)*

**(\*) Disponibile in tutti i colori**  
Disponibles dans toutes les couleurs  
In allen Farben erhältlich  
Available in all colours  
Disponibile en todos los colores  
Доступна во всех цветах



**Green Building Council**  
Ceramiche Supergres  
è socio ordinario del GBC Italia



**Ceramic Tiles of Italy**

CERAMICHE  
**SUPERGRES**  
**MADE in ITALY**